

## AIRDRAULIC BIRCO GROUP PTY LTD

**Sydney (H.O.):** Unit 1, 33-35 Lwr Gibbes Street Chatswood NSW 2067 Phone: 61 2 9882 3444 Fax: 61 2 9882 3133 **Brisbane:** Unit 27, 121 Kerry Road, Archerfield QLD 4108

Phone: 61 7 3255 6188 Fax: 61 7 3255 6199

Melbourne: 165 Clayton Rd, Clayton VIC 3168

Phone: 61 3 9544 1711 Fax: 61 3 9544 2111

Perth: Unit 2, 73 Poole Street, Welshpool WA 6106

Phone: 61 8 9258 4144 Fax: 61 8 9258 425

Website: www.abgpl.com.au

Email: sales@abgpl.com.au





ABN 47 002 890 477



## GP 12108 Breaker

Used in light to medium construction, utility and plant maintenance work such as light demolition of floors, pavements and road surfaces as well as various other service jobs. They are also often found on bridge deck jobs.

Although classed as a 35-pound tool, the CP 1210 offers the hitting power and high performance of a larger tool. In addition to the standard units.

There are also "Hushed Power" versions (*S models*) and versions with extra vibration dampening (*SVR models*).

## Key Features:

- Tuned valve system gets more power out of your breaker and increases productivity
- Improved modern design for excellent durability
- Four-bolt backhead withstands rugged use
- Reversible piston reduces maintenance cost
- Lubrication grooves on the piston increases the service life of the tool and its major parts
- New swivel design for increased manoeuvrability
- New type of heavy-duty front head springs reduce maintenance cost
- "Hushed power" versions equipped with mufflers (S-models)
- Versions with improved vibration dampening system (SVR models)



Model	Weight (kg)	Length mm	Air Consumption I/s	Blows Per Minute (BPM)	Vibration Level 3 Axes (ISO 20643) m/s²	Sound Power Level Guaranteed (2000/14/EC) dB(A)	Sound Pressure Level (ISO 11203) dB(A)	Air Inlet	
CP1210S	22.5	585	26.5	1400	14.6	105	92	3/4 NPTF	

## **DISTRIBUTORS OF:**