

AIRDRAULIC BIRCO GROUP PTY LTD

Sydney (H.O.): Unit 1, 33-35 Lwr Gibbes Street Chatswood NSW 2067 Phone: 61 2 9882 3444 Fax: 61 2 9882 3133

 Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108

 Phone: 61 7 3255 6188
 Fax: 61 7 3255 6199

 Melbourne: 165 Clayton Rd, Clayton VIC 3168

 Phone: 61 3 9544 1711
 Fax: 61 3 9544 2111

 Perth: Unit 2, 73 Poole Street, Welshpool WA 6106

 Phone: 61 8 9258 4144
 Fax: 61 8 9258 425

Website: www.abgpl.com.au Email: sales@abgpl.com.au





ABN 47 002 890 477



GP 1260S Breaker

For use in tough construction and plant maintenance work areas such as breaking reinforced concrete, heavy road work, cutting tarmac, frozen ground or non-consolidated rock & general demolition work. These new 60-pound breakers continue the tradition of the well-known CP 1230 and CP 1240 with outstanding robustness and reliability in tough working conditions. Plus, they offer more power and are lighter weight.

Key Features:

- Even more power and productivity than the CP 1230 and CP 1240
- Improved modern design for excellent durability
- Four-bolt backhead withstands rugged use
- Integral oiler provides continuous lubrication
- Reversible piston reduces maintenance cost
- New swivel design for increased manoeuvrability
- New type of heavy-duty front head springs reduce maintenance cost
- "Hushed power" versions equipped with mufflers (S-models)
- Versions with improved vibration dampening system (SVR models)





Model	Weight (kg)	Length mm	Air Consumption I/s	Blows Per Minute (BPM)	Vibration Level 3 Axes (ISO 20643) m/s ²	Sound Power Level Guaranteed (2000/14/EC) dB(A)	Sound Pressure Level (ISO 11203) dB(A)	Air Inlet
CP 1260S	31	680	34.5	1300	20.7	110	97	3/4 NPTF

DISTRIBUTORS OF: