



## AIRDRAULIC BIRCO GROUP PTY LTD

**Sydney (H.O.):** Unit 1, 33-35 Lwr Gibbes Street Chatswood NSW 2067

Phone: 61 2 9882 3444 Fax: 61 2 9882 3133

**Brisbane:** Unit 27, 121 Kerry Road, Archerfield QLD 4108

Phone: 61 7 3255 6188 Fax: 61 7 3255 6199

**Melbourne:** 165 Clayton Rd, Clayton VIC 3168

Phone: 61 3 9544 1711 Fax: 61 3 9544 2111

**Perth:** Unit 2, 73 Poole Street, Welshpool WA 6106

Phone: 61 8 9258 4144 Fax: 61 8 9258 4255








Website: [www.abgpl.com.au](http://www.abgpl.com.au) Email: [sales@abgpl.com.au](mailto:sales@abgpl.com.au)

ACN 002 890 477

ABN 47 002 890 477



# BAUER TYPE COUPLINGS

Diagram & Description	Size	Code
 Ball With Hose Tail (Galvanised)	50 mm	B2-BT
	75 mm	B3-BT
	100 mm	B4-BT
	150 mm	B6-BT
	200 mm	B8-BT
 Socket With Hose Tail (Galvanised)	50 mm	B2-ST
	75 mm	B3-ST
	100 mm	B4-ST
	150 mm	B6-ST
	200 mm	B8-ST
 Lever Closing Ring (Galvanised)	50 mm	B2-CRG
	75 mm	B3-CRG
	100 mm	B4-CRG
	150 mm	B6-CRG
	200 mm	B8-CRG
 Lever Closing Ring (Black)	50 mm	B2-CRB
	75 mm	B3-CRB
	100 mm	B4-CRB
	150 mm	B6-CRB
	200 mm	B8-CRB
 Sealing O Ring (Rubber)	50 mm	B2-OR
	75 mm	B3-OR
	100 mm	B4-OR
	150 mm	B6-OR
	200 mm	B8-OR
 Weld On Ball (Black)	50 mm	B2-WOB
	75 mm	B3-WOB
	100 mm	B4-WOB
	150 mm	B6-WOB
	200 mm	B8-WOB
 Weld On Socket (Black)	50 mm	B2-WOS
	75 mm	B3-WOS
	100 mm	B4-WOS
	150 mm	B6-WOS
	200 mm	B8-WOS

The Bauer type fittings are a wonderful addition for hose applications. The fast connection allows easy set-up and tear-down.

Uneven terrain is no problem because of the fittings ability to articulate. It means an exceptional easy fitting to couple hoses together or to pumps and tanks.

Users appreciate the longer shank lengths allowing a more secure attachment to the hose. The fast ball and socket connection provides a simpler and much easier attachment even when covered with slippery material.

They are designed to maintain high tensile strength under pressure or suction.

### **FAST**

No loose parts and an easy hook-and-latch design means you can quickly attach pipe with no tools. Even in the dark!

### **FLEXIBLE**

The unique ball and socket design allows up to a 30 degree articulation at the pipe joint. That makes it easy to align pipe over uneven terrain. Articulation on 6" and 8" fittings is 15 degrees.

### **SAFE**

The Bauer type coupler provides a tight seal for suction and pressure situations up to 290 psi. The Safety Pin Option provides a positive lock against accidental release of a coupler.

### **STRONG AND DURABLE**

Produced from high-grade high-tensile steel with abrasion resistant hot-dip galvanization in accordance with DIN 50976.

### **PRESSURE RATING**

Pressure capability is 290 PSI for fittings up through 4" and 174 PSI for larger diameters.

### **HEAT RATING**

They will resist high heat up to 110°C.

### DISTRIBUTORS OF:

\*Edco Surface Preparation Tools \*Macdonald Air Tools \*Timberking Chainsaws \*Rock Drills \*Drilling Equipment \*Picket Post Driver \*Air Hose & Fittings  
\*Compressors \*ASL Lubricators \*Stone Compaction Equipment \*Electric & Pneumatic Points & Chisels \*Pedestal & Wall Fans \*Mancoolers & Tube Fans  
\*VAF Fans \*Venturi Air Movers \*Gas Heaters \*Submersible Pumps \*Transfer Pumps \*Puddle Pumps \*Layflat hose and fittings \*Bauers & Camlocks  
\*Blast Hole Plugs \*Anfo Loaders \*Slopemeters \*Schroeder Hydraulic Filters & Elements \*CBC Reversing Cameras \*Reversing Alarms \*Osha Safety Valve