



AIRDRAULIC BIRCO GROUP PTY LTD

Sydney (H.O.): Unit 1, 33-35 Lwr Gibbes Street Chatswood NSW 2067

Phone: 61 2 9882 3444 Fax: 61 2 9882 3133

Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108

Phone: 61 7 3255 6188 Fax: 61 7 3255 6199

Melbourne: 165 Clayton Rd, Clayton VIC 3168

Phone: 61 3 9544 1711 Fax: 61 3 9544 2111

Perth: Unit 2, 73 Poole Street, Welshpool WA 6106

Phone: 61 8 9258 4144 Fax: 61 8 9258 4255

Website: www.abgpl.com.au Email: sales@abgpl.com.au



ACN 002 890 477

ABN 47 002 890 477



Turbo Grinders

TMC-7

For edge grinding along vertical surfaces and removing coatings, build-ups, markings, overlays or paints

- 180mm working width will grind approximately 130 – 165 lineal metres per hour at 1.5mm with an EDCO diamond Cup Wheel
- Three-position articulating frame adjustment for left angle, right angle or straight position grinding
- Four-position dust shroud allows flush grinding against any vertical surface in the left angle, right angle or straight position
- Multiple-position handle assembly allows the operator to work behind the unit for edge grinding or in front of the unit and control the amount of grinding pressure applied
- Adjustable tubular handle construction provides operator maximum grinding flexibility and allows for complete clearance of any vertical surface
- Available with 2.0 HP electric motor
- Comes standard with Flex Head Assembly, but is also available with optional Rigid Head Assembly for doing gutter work
- New & improved tapered roller bearings provide less maintenance and longer life



STANDARD FLEX HEAD ASSEMBLY IS IDEAL FOR:

- Preparing a smooth, flat floor to receive a new coating
- Removing coatings
- Grinding rough concrete surfaces
- Grinding surfaces 4 times faster than a traditional floor grinder

**EDCO Grinders -
Proven since
1959**

TG-10

Four times faster than conventional grinders.

- 250mm working width will grind approximately 37-47 sq. metres per hour at 1.5mm with an EDCO Diamond Disc
- Grind wet or dry
- Includes 250mm Diamond Disc & standard vacuum port
- Rounded shroud allows you to grind within 12mm of any vertical surface and also provides better dust control
- Less torque on operator
- Tapered roller bearings have improved seals for longer life and less maintenance



STANDARD RIGID HEAD ASSEMBLY IS IDEAL FOR:

- Grinding uneven expansion joints, high spots, joint curls and bridge decks
- Removing coatings
- Grinding rough concrete surfaces

Model	Part #	Power	Horse Power	* RPM's	Belts	Length	Width	Height	Weight
TMC-7	57200-50	Single ph. electric	2 HP	1740	Cgd "V" Belts	102 cm	61 cm	98 cm	59 kg
TG-10, 5B	56800-50	3 phase electric	5 HP	2275	Std. "V" Belts	109 cm	53 cm	94 cm	95 kg
TG-10, 11H	56600	Petrol	11 HP	2520	Std. "V" Belts	109 cm	53 cm	94 cm	82 kg

DISTRIBUTORS OF:

*Edco Surface Preparation Tools *Macdonald Air Tools *Timberking Chainsaws *Rock Drills *Drilling Equipment *Picket Post Driver *Air Hose & Fittings
*Compressors *ASL Lubricators * Stone Compaction Equipment *Electric & Pneumatic Points & Chisels *Pedestal & Wall Fans *Mancoolers & Tube Fans
*VAF Fans *Venturi Air Movers *Gas Heaters *Submersible Pumps *Transfer Pumps *Puddle Pumps *Layflat hose and fittings *Bauers & Camlocks
*Blast Hole Plugs *Anfo Loaders *Slopemeters *Schroeder Hydraulic Filters & Elements *CBC Reversing Cameras *Reversing Alarms *Osha Safety Valve