

AIRDRAULIC BIRCO GROUP PTY LTD

Street Chatswood NSW 2067 Sydney (H.O.): Unit 1, 33-35 Lwr Gibbes Phone: 61 2 9882 3444 Fax: 61 2 9882 3133 Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108 Phone: 61 7 3255 6188 Fax: 61 7 3255 6199

Melbourne: 165 Clayton Rd, Clayton VIC 3168 Phone: 61 3 9544 1711 Fax: 61 3 9544 2111 Perth: Unit 2, 73 Poole Street, Welshpool WA 6106 Phone: 61 8 9258 4144 Fax: 61 8 9258 4255 Website: www.abgpl.com.au Email: sales@abgpl.com.au







ACN 002 890 477 ABN 47 002 890 477



Features:

- Available in 5 head versions.
- Delivers 1,200 hits per minute for fast surface removal.
- Requires only 160 CFM at 100 PSI (Supplied with Automatic in-line oiler
- Heavy-duty 6mm steel frame.
- Wide T-Grip Handle and 20cm wheels for superior balance and handling
- 75mm Vacuum Port for dust-free operation.
- WHIPCHEK Cable assures safe air hose hook-up.

Ideal for:

- Removing spalling concrete and loose or deteriorated concrete.
- Roughening surfaces for laying new concrete over existing surface.
- Reducing high spots.
- Creating wheelchair access ramps.
- Removing epoxy.
- Creating slip-resistant surfaces or texturing parking garage ramps.

Performance:

5 Scabbler heads provide 280mm working width.

- Removes up 6mm of concrete in a single pass.
- The typical removal rate with a 30mm working width is 18 to 24 square metres per hour at a 3mm depth.

•	•		

Model	Part #	Power	Horse Power	Length	Width	Height	Weight			
CD-5	63100	Air	160 CFM at 100 PSI	112cm	75cm	102cm	136kg.			
	•	•			•					
SCAPPIED ACCESSORIES										



DISTRIBUTORS OF: