

AIRDRAULIC BIRCO GROUP PTY LTD

 Sydney (H.O.): Unit 1, 33-35 Lwr Gibbes
 Street Chatswood
 NSW 2067

 Phone: 61 2 9882 3444
 Fax: 61 2 9882 3133

 Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108

 Phone: 61 7 3255 6188
 Fax: 61 7 3255 6199

Melbourne: 165 Clayton Rd, Clayton VIC 3168
Phone: 61 3 9544 1711
Perth: Unit 2, 73 Poole Street, Welshpool WA 6106
Phone: 61 8 9258 4144
Fax: 61 7 3255 6199
Fax: 61







ACN 002 890 477 ABN 47 002 890 477



Floor Grinders

Single and Dual Disc

Features:

- Round shroud gets tight against walls (SEC)
- Easy-rolling 25 cm steel-core, rubber wheels
- New lifting eye for easy loading and unloading
- New 8m. power cord attached with cord hanger
- Power cord retainer keeps cord from pulling out of starter box
- Accessory Toolbox tray on the SEC
- New side-mounted lifting handles
- Counter-rotating discs on the 2EC prevent machine from pulling side to side and give operator greater control
- Easier access to grease fittings
- Remote access multi-vac port hookup for dust control
- Water hookup for dust control
- · Rugged and easy to maintain

Ideal for:

- Residential applications
- Grinding concrete
- Repairing damaged concrete slabs
- Removing urethanes or epoxy thin-coats
- Leveling high spots or surface imperfections
- Smoothing rough surfaces, rain marks or trowel marks
- Removing mastics, thin-sets, paint build-ups, resins and more





EDCO Grinders -Proven since 1959

Production Rate:

SEC-2B 280mm working width will grind approx. 18 – 24 sq.m/hr with EDCO Dyma-Serts

2EC-2B 560mm working width will grind approx. 36 – 48 sq.m/hr with EDCO Dyma-Serts

Model	Part #	Power	Horse Power	Phase	Amps	* RPM's	Length	Width	Height	Weight
SEC-2B	52500	Electric	2 HP, 230 V	Single (50Hz)	10	475	104cm	61cm	92cm	82kg.
2EC-2B	51300	Electric	2 HP, 230 V	Single (50Hz)	10	190	120cm	68cm	98cm	107kg

DISTRIBUTORS OF: