



AIRDRAULIC BIRCO GROUP PTY LTD

Sydney (H.O.): Unit 1, 33-35 Gibbes Street Chatswood NSW 2067

Phone: 61 2 9882 3444 Fax: 61 2 9882 3133

Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108

Phone: 61 7 3255 6188 Fax: 61 7 3255 6199

Melbourne: 165 Clayton Rd, Clayton VIC 3168

Phone: 61 3 9544 1711 Fax: 61 3 9544 2111

Perth: Unit 2, 73 Poole Street, Welshpool WA 6106

Phone: 61 8 9258 4144 Fax: 61 8 9258 4255

Website: www.abgpl.com.au **Email:** sales@abgpl.com.au

A B N 47 002 890 477

A C N 002 890 477



VAF-16E

405mm (16") VANE AXIAL FAN

240V

There are two things to consider about structural drying:

- 1. More air movement is better.** One of the industries more colourful instructors like to ask the question of his students, "What are the two most important elements if drying?" His answer, "Air movement & air movement!" While restoration professionals know that there are many factors that must be balanced to achieve as good drying environment, you must evaporate moisture faster.
- 2. Less amps means an easier setup.** Why do some jobs end up with less air movement than the ideal? Because lots of air movement can be difficult to achieve due to the limited amount of power available on many sites. The simple answer is the VAF16E.
At 2.5 amps, tripping breakers is a thing of the past



As with its smaller brother, the VAF12E, it is most often used to exhaust moisture laden air or to introduce drier outdoor air, axial fans can also be used as ventilators, circulators and simply as fans. Used to push or pull air-positive or negative air displacement with great force. Perfect for exhausting fumes, ventilating confined spaces and perimeter crawl spaces

Features:

- **Draws only 2.5 Amps**
- **Run up to 6 fans on a 15 amp circuit**
- **68% More Airflow***
- **48% Less Amps**
- **Durable, Lightweight Polyethylene Shell**
- **Designed for easy maintenance**
- **Interlocking ribs for stacking vertically**

* Compared to the best selling centrifugal air mover in USA

Specifications

Amps	Air Flow	Blade Size	Motor	Frequency	Power Cord	Stackable	Dimensions	Weight
2.5	2260 CFM 1067 l/s	16" 405 mm	Electric ¼ HP	50HZ	6 Mtr	YES	55 x 53 x 40 cm's	15 Kgs

DISTRIBUTORS OF:

*Edco Surface Preparation Tools *Macdonald Air Tools *Timberking Chainsaws *Rock Drills *Drilling Equipment *Picket Post Driver *Air Hose & Fittings
 *Compressors *ASL Lubricators * Stone Compaction Equipment *Electric & Pneumatic Points & Chisels *Pedestal & Wall Fans *Mancoolers & Tube Fans
 *VAF Fans *Venturi Air Movers *Gas Heaters *Submersible Pumps *Transfer Pumps *Puddle Pumps *Layflat hose and fittings *Bauers & Camlocks
 *Blast Hole Plugs *Anfo Loaders *Slopemeters *Schroeder Hydraulic Filters & Elements *CBC Reversing Cameras *Reversing Alarms *Osha Safety Valve