



AIRDRAULIC BIRCO GROUP PTY LTD

Sydney (H.O.): Unit 1, 33-35 Gibbes Street Chatswood NSW 2067

Phone: 61 2 9882 3444 Fax: 61 2 9882 3133

Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108

Phone: 61 7 3255 6188 Fax: 61 7 3255 6199

Melbourne: 165 Clayton Rd, Clayton VIC 3168

Phone: 61 3 9544 1711 Fax: 61 3 9544 2111

Perth: Unit 2, 73 Poole Street, Welshpool WA 6106

Phone: 61 8 9258 4144 Fax: 61 8 9258 4255

Website: www.abgpl.com.au **Email:** sales@abgpl.com.au




A B N 47 002 890 477

A C N 002 890 477

Pneumatic Chain Saws

- Australian Manufactured
- Silenced
- Lightweight
- Powerful
- Pressure fed chain lubrication
- Special models available for:
 - Coal Mining
 - Underwater Use



The Timberking pneumatic chain saw was specifically designed for underground mine use, but has been widely accepted in the building and construction industries, shipyards and marine environments, particularly underwater, railways, quarries and timber mills – in fact anywhere compressed air is available.

As certain countries prohibit the use of aluminium in coalmines, the Timberking Chain Saw has been produced in two (2) body materials, i.e. Aluminium for lightweight and zinc-based material for those environs where aluminium is prohibited.

The body and handle are sand-cast, which produces a stronger more durable unit. The high torque pneumatic motor has been designed around a six-bladed rotor specifically for this application.

In keeping with continuing development, we have recently incorporated various components including:

- Acoustic exhaust silencer
- Pressurised chain lubrication with adjustable flow valve to enable various viscosities of oil to be used
- Increased metal sections in high impact areas
- Simplified throttle valve operation

Specifications	
Air pressure	100PSI (7 bar)
Motor Output	6HP SAE (4.47kw)
Speed	3800 RPM
Air Consumption	110 CFM (51.9 l/s @100PSI)
Inside Hose diameter	19 mm (3/4")
Guide bar (standard)	43 cm (17")
Saw Chain	0.404 pitch x 0.063 gauge
Chain Lubrication	Pressure fed - adjustable
Tank Capacity	0.49 litre
Weight c/w 17" guide bar (Aluminium)	8.2 kg (18 lbs)
Weight c/w 17" guide bar – Zamac	13.1 kg (29 lbs)

Optional Extras
Chain bar nose guard
Fixed top protection bar
Swing-up top protection bar
Underwater attachment
In-line lubricator
Tungsten carbide chain
Front hand protector
15", 21" or 25" bar and chain

DISTRIBUTORS OF:

*Edco Surface Preparation Tools *Macdonald Air Tools *Timberking Chainsaws *Rock Drills *Drilling Equipment *Picket Post Driver *Air Hose & Fittings
*Compressors *ASL Lubricators *Stone Compaction Equipment *Electric & Pneumatic Points & Chisels *Pedestal & Wall Fans *Mancoolers & Tube Fans
*VAF Fans *Venturi Air Movers *Gas Heaters *Submersible Pumps *Transfer Pumps *Puddle Pumps *Layflat hose and fittings *Bauers & Camlocks
*Blast Hole Plugs *Anfo Loaders *Slopemeters *Schroeder Hydraulic Filters & Elements *CBC Reversing Cameras *Reversing Alarms *Osha Safety Valve