

AIRDRAULIC BIRCO GROUP PTY LTD Sydney (H.O.): Unit 1, 33-35 Lwr Gibbes Street Chatswood N

Street Chatswood NSW 2067

Phone: 61 2 9882 3444 Fax: 61 2 9882 3133 Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108 Phone: 61 7 3255 6188 Fax: 61 7 3255 6199 Melbourne: 165 Clayton Rd, Clayton VIC 3168

Phone: 61 3 9544 1711 Fax: 61 3 9544 2111 Perth: Unit 2, 73 Poole Street, Welshpool WA 6106 Phone: 61 8 9258 4144 Fax: 61 8 9258 4255 Website: www.abgpl.com.au Email: sales@abgpl.com.au





ABN 47 002 890 477

FIRE FIGHTING PU

TOP PERFORMANCE WHEN YOU NEED IT!





- Cast aluminium alloy pump with 40mm (1.1/2") inlet
- Three way outlet, consisting of 1 x 40mm (1.1/2") outlet and 2 x 25mm (1") outlets
- Also available with 2" inlet and 2" outlets.

FEATURES:

- Cast aluminium impeller gives improved life.
- Bolt on replaceable suction port so enabling easy and quick replacement if inlet cracked or thread is damaged.
- Cast iron diffuser increases pump life and greatly reduces maintenance.
- Metal (not plastic) delivery outlet caps.
- High quality cast aluminium pump body, for longer life and less maintenance.
- Spark arrestor muffler.
- Double fuel filter system to protect engine from any water or impurities.
- A serviceable carburettor, not a "throw-away", reduces costs.
- Double ball bearing crankshaft, increasing engine life.
- Pointless ignition system.
 - Less maintenance.
 - Easier starting.
 - More reliability.
- Cast iron cylinder liner, extends engine life by allowing rebore.



AIRDRAULIC BIRCO GROUP PTY LTD Sydney (H.O.): Unit 1, 33-35 Lwr Gibbes Street Chatswood N

Street Chatswood NSW 2067

Phone: 61 2 9882 3444 Fax: 61 2 9882 3133 Brisbane: Unit 27, 121 Kerry Road, Archerfield QLD 4108 Phone: 61 7 3255 6188 Fax: 61 7 3255 6199 Melbourne: 165 Clayton Rd, Clayton VIC 3168 Phone: 61 3 9544 1711 Fax: 61 3 9544 2111

Perth: Unit 2, 73 Poole Street, Welshpool WA 6106 Phone: 61 8 9258 4144 Fax: 61 8 9258 4255 Website: www.abgpl.com.au Email: sales@abgpl.com.au







ACN 002 890 477 ABN 47 002 890 477

ADDITIONALLY:

- Single and Twin Impeller.
- Petrol and Diesel Models.
- Powered by Subaru engines.
- Available in recoil and electric start.
- Roll over protection frame available.
- Hose kits available.
- Both the engine and the pump come with a 2-year warranty.

	Petrol Powered	Diesel Powered
Pump Type	Single Impellor	Single Impellor
Suction	38mm	38MM
Delivery	38mmx1, 25mmx2	38mmx1, 25mmx2
Total Head	63m	57m
Max Volume	300 Litres/Minute	300 Litres/Minute
Suction Head	8m	8m
Engine	Subaru (Robin)	SUBARU DY27-2d 5.5HP
Model	EY20	DY27
Туре	Air Cooled 4-Stroke Gasoline	Air Cooled, 4-Stoke Diesel
Fuel	Unleaded Gasoline	Diesel Light Oil
Fuel Capacity	3.8L	3.2L
Starting System	Recoil Starter	Recoil Starter
Weight	30kg	48kg